

SECTION 00620 - COLD PLANE PAVEMENT REMOVAL

(Follow all instructions. If there are no instructions above a subsection, paragraph, sentence, or bullet, then include them in the project but make necessary modifications to only include project specific specifications. Delete specifications that do not apply to the project.)

~~*(Use the following paragraph when subsections .40, .40(b), and .42 are NOT included in the project.)*~~

Comply with Section 00620 of the Standard Specifications.

~~*(Use the following lead-in paragraph when subsections .40 and .40(b), or .42 are included in the project.)*~~

Comply with Section 00620 of the Standard Specifications modified as follows:

(Use the following subsections .40 and .40(b) when cold planed areas are required to be paved the same day of cold plane pavement removal. Check with pavement design for use of these subsections.)

00620.40 Pavement Removal - Replace paragraphs (b), (c), (d), and (e) with the following paragraph (b):

(b) Removal and Replacement - Repave all cold-planed areas during the same work shift.

~~*(Use the following subsection .42 when materials are to be recycled. List stockpile sites.)*~~

00620.42 Disposal of Materials - Replace this subsection, except for the subsection number and title, with the following:

Dispose of all materials according to 00290.20.

(Use the following paragraph and bullet when materials are to be recycled. List stockpile sites.)

Add the following paragraph to the end of this subsection:

When existing pavement is to be removed in more than one thickness or lift and is to be recycled into asphalt concrete mixture, either on this Project or a future project, place the material from each thickness or lift in separate stockpiles at the following sites:

-