

SP850 (~~03-3106-26-08~~)

(When this Section is used on a project and when it has a completion date of September 15 or later, contact the Scheduler to determine if a separate completion date for striping is required. If a separate completion date is required, include an interim completion date in 00180.50(h).)

SECTION 00850 - COMMON PROVISIONS FOR PAVEMENT MARKINGS

(Follow all instructions. If there are no instructions above a subsection, paragraph, sentence, or bullet, then include them in the project but make necessary modifications to only include project specific specifications. Delete specifications that do not apply to the project.)

Comply with Section 00850 of the Standard Specifications modified as follows:

(Use the following subsection .20(c) when inlaid/grooved markings are required.)

00850.20(c) Equipment for Inlaid/Grooved Markings - Replace this subsection, except for the subsection number and title, with the following:

Use grinding equipment with diamond grinding heads and shot-blasting equipment to create a smooth, flat-bottomed cut of uniform depth or a sloped cut as shown.

00850.46 Placement Tolerance - Replace the bullet that begins "Thickness of lines..." with the following bullet:

- **Thickness of lines:** + 1/3 of the specified thickness, – 1/10 of the specified thickness

00850.47(c) Retroreflectivity - Replace the sentence that begins "Use a retroreflectometer..." with the following sentence:

Use a 30 meter geometry retroreflectometer to measure the retroreflectivity within 48 hours of curing and 14 calendar days after placement, except for paint applications:

[00850.70 Disposal of Waste - Replace this subsection with the following subsection:](#)

[00850.70 Disposal of Materials - Dispose of all materials according to 00290.20.](#)