State of Oregon Department of Environmental Quality Water Quality Division, Onsite Program



Dosing Tank <1,000 Gallons Engineered Plan Requirements/Self Certification Form

Note: Refer to OAR 340-71&73 for details of a specific rule requirement itemized on the checklist. Specifications identified on the checklist must be clearly shown on the engineering plans submitted.

Tank Capacity & Configuration:

- Tank volume (in gallons) below invert:_____, operating gallons:_____, gallons per inch calculated by Engineer:_____. OAR 340-73-0025(11) *These and subsequent details must be shown on the plans.*
- Buoyancy and countermeasures described where on plans:______. 73-0025(11)
- Watertight testing procedure described where on plans:______. 73-0025(3)
- Service access manhole diameter: ____inches (18 inch minimum). 73-0025(2)
- Service riser/gasketed cover described & detailed where on the plans:______. Riser connection at tank described where on the plans:______. 73-0025(2)
- Diameter service access riser: _____inches (20 inch minimum). 71-0220(6)(c)
- Inlet fitting materials:______ (Sch. 40 PVC or ABS?). Diameter:__inches (4 inch minimum). 73-0025(7)(a)
- Air gap above inlet fitting:____inches (2 inch minimum). Watertight attachment? Y/N____ 73-0025(7)(f)
- Inlet fitting extends _____inches below lowest operating liquid level. 73-0050(6)
- Method for watertight pipe connections described where on the plans:______. 73-025(7)(i)
- Electrical and outlet piping pass-through described where on the plans:______. 73-0050
- Pump control/alarm float placement provides adequate capacities for surge clearly shown/described on plans? Y/N where: ______ (1/3 design flow reserve storage minimum that allows for sludge & scum accumulation, and hydraulic retention time without exceeding inlet invert level). 73-0055(4)
- Commercial-use tank designed for placement of 2 pumps, with adequate service access? Y/N_ 73-0050(4)
- Structural integrity described by engineer. The tank can support an earth load of _____pounds/square foot (300 psf minimum) lateral load _____pounds per cubic foot of equivalent fluid pressure (62.4 pcf of EFP) _____pound wheel load (2,500 pound minimum shall be considered)73-0025 (5)

08-WQ-011

Note: Refer to OAR 340-71&73 for details of a specific rule requirement itemized on the check-list. **Specifications identified on the check-list must be clearly shown on the engineering plans submitted.**

INSTALLATION MANUAL

•	Method of protection from the weather: (example would be water	proof paper) 73-0025(13)
•	Excavation details for tank placement described where on the guide:	. 73-0025(13)
•	Tank bedding requirements described where on the guide:	71-0220(3)(b)
•	Tank backfill procedures described where on the guide:	73-0025(13)
•	Buoyancy and countermeasures described where on the guide:	. 73-0025(11)
•	Guidance provided for water-tight attachment of Riser to top of tank described where guide: 73-0025(13)	on the
•	Guidance provided for secure attachment of riser cover described where on the guide: 73-0025(13)	
•	Guidance provided for attachment of outlet piping described where on the guide: 73-0025(13)	
•	Water-Tight testing protocols described where on the guide:	. 73-0025(13)
•	Special precautions or limitations described in manual? Y/N 73-0025(13)	
•	Guidance provided for placement of pump control floats, valves, wiring, or siphon and counter (if applicable) described where on the guide: 73-0050(4 & 5) & 73-0055(5)	
•	Pump control/alarm float placement that provides adequate capacities for surge, and a described where on the guide: 73-0055(4).	dequate storage volume

Certification. I hereby certify that the engineering plan(s) and specifications as well as installation guide that I have submitted for the tank configuration are complete and in total compliance with pertinent requirements of the OAR 340-71& 73 Onsite Wastewater Treatment System Rules.

Manufacturer

Signature:	Title:	Date:
Engineer		
Signature:	Title:	Date: